

MANSIL-ZX[®]

SYNTHETIC SODIUM ALUMINO SILICATE



DESCRIPTION

Fine Particle Amorphous Synthetic Sodium Alumino Silicate

F/QA/9.0/01

SPECIFICATIONS

Sr. No.	Physico- chemical Properties	Unit	Specification	Test method
1	Appearance	--	Fine White powder	Visual
2	Oil absorption (Linseed oil)	ml/100g	110 min	ISO787/5
3	Avg. Particle size (d50)	µm	7.0 max	By laser diffraction
4	Moisture content (at 105 °C)	%	6.0 Max	ISO787/2
5	pH (5% water suspension)	--	10 - 11.5	ISO 787/9
6	Ignition Loss at (105 -1000 deg C)	%	14.0 max	ISO 3262/11
7	BET Surface Area	M ² /g	40 - 80	ISO 5794-1/D
8	Tapped bulk density	g/l	250 ± 50	ISO 787 /11
9	Residue on 325 # Sieve (Wet residue)	%	0.1 max	GMGB

APPLICATIONS :- " As Ti₂ Extender for water and solvent based Paints to improve Opacity, Whiteness, Weathering resistance and storage stability of Paints"

PACKING & LOGISTICS	GRADE	NET WEIGHT (KGS)	SHIPMENTS (MT)				
			TRUCK LOAD	CONTAINER LOAD			
				UN PALLETIZED		PALLETIZED	
				20'FCL	40' FCL	20'FCL	40' FCL
MANSIL ZX	25.0	9 MTS	10 MTS	22.0 MTS	7.2 MTS	19.2 MTS	



Block No. 395, Tejpur Road, At & Post - Martoli - 384430,
 Ta. : Jotana, Dist : Mahesana.
 Tel. No. +91-2762-225566, (M) 9687674740,
 Fax No. : +91 2762 225544
 E-mail : madhavind15@gmail.com

An ISO 9001:2015, ISO 22000:2005 Certified Company



Science in the service of Industry & Environment